

Steam bent timbers:

Master timber in way of mast & timber each side of it - 60 sided x 25 moulded
 Remainder of timbers - 35 sided x 25 moulded
 All at 155 centre to centre.

Floors:

Laminated floors 25 sided x 55 moulded depth on centreline are located on alternate timbers for 3/5 rule length and thereafter every third timber. But see floors drawing for details.



- General Notes:**
1. All dimensions are in millimetres unless otherwise noted.
 2. The Zero Point is the intersection of the Datum Water Line (dwl) with the stemface.
 3. Positions are measured fwd and aft (marked "-") of the Zero Point.
 4. Heights are measured above and below (marked "+/-") the dwl.
 5. Offsets are measured each side of the fore-&-aft centreline (marked "c" or c/line).
 6. Waterlines are designated "wl" followed by their height.
 7. Buttocks are designated "b" followed by their offset.
 8. Diagonals are designated "d" followed by their start height on the centreline and their angle to it.
 9. Offsets on diagonals are measured down the angle of the diagonal.
 10. Offsets are to inside of skin unless noted otherwise.

Whisstock
boats and boat plans
support@whisstock.com

Boat 140 Locations of Temporary Moulds	Scale 1/10
	Date 14/11/2009
	Plan No. 140/003/09
	Issue No. 01 web
	Drawing Size 895 x 305 - 35" x 12"

© Bmarkweb Ltd 2009. All Rights Reserved